

SELECTION: Industrial Monitor (rugged, IP65)

- Aluminium front panel meet IP65 standard
- Robust steel chassis for shocking and vibration requirements
- Long lifetime
- High brightness
- Advanced thermal and air flow design
- OSD function with keys in the front panel
- Operation temperature from 0 ~ +50°C
- optional: 9 ~ 36 V DC power input for mobile application
- optional: Touch screen
- Panel mount, rack mount, wall mount or arm mount

Model	DM-65GS	DM-84GS	DM-104GS	DM-121GS	DM-150GS	DM-170GS	DM-190GS
Size	6.5"	8.4"	10.4"	12.1"	15"	17"	19"
Input Interface	Analog VGA	Analog VGA	Analog VGA	VGA + DVI-D	VGA+ DVI-D	VGA+ DVI-D	VGA+ DVI-D
Resolution	640 x 480	800 x 600	800 x 600	800 x 600	1024 x 768	1280x1024	1280x1024
Brightness (cd/m ²)	400/ 500	220/ 450	230/ 400	400	350	300	300
Contrast	550 : 1	500 : 1	500 : 1	500 : 1	400 : 1	500 : 1	700 : 1
Color	262K	262K	262K	262K	262K	16.2M	16.2M
Pixel (mm)	0.207	0.213	0.264	0.307	0.297	0.264	0.294
Frontframe	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Chassis	Heavy duty steel	Heavy duty steel	Heavy duty steel	Heavy duty steel	Heavy duty steel	Heavy duty steel	Heavy duty steel
View Angel (H/V)	140/120	130/110	120/100	140/110	120/100	140/130	140/130
Input Voltage	12VDC	12VDC	12VDC	12VDC o. 9 ~ 36VDC	12VDC o. 9 ~ 36VDC	12VDC o. 9 ~ 36VDC	12VDC o. 9 ~ 36VDC
OSD	yes	yes	yes	yes	yes	yes	yes
Mounting	Wall/Arm/ Panel/ Rack/DIN	Wall/Rack/ Panel/Arm	Wall/Rack/ Panel/Arm	Wall/Rack/ Panel/Arm	Wall/Rack/ Panel/Arm	Wall/Rack/ Panel/Arm	Wall/Rack/ Panel/Arm
Color	Silver	Silver	Silver	Silver	Silver	Silver	Silver
Dim. / mm (B x H x T)	183 x 143 x 41	244 x 178 x 49	312 x 242 x 53	340 x 260 x 58	410 x 309 x 65.1	452 x 356 x 65.2	482 x 399 x 73
Operation temperatur	0 ~ +50°C	0 ~ +50°C	0 ~ +50°C	0 ~ +50°C	0 ~ +50°C	0 ~ +50°C	0 ~ +50°C
P Level	IP65	IP65	IP65	IP65	IP65	IP65	IP65
NG Weight	1 kg	1.8 kg	3 kg	3.8 kg	6 kg	8.6 kg	10 kg
Power Adapter	25 W	25 W	25 W	45 W	45 W	45 W	45 W
Panel Cut-in mm	179 x 139	232 x 166	290 x 220	312 x 232	385 x 285	424 x 330	449 x 362